

Green and black silicon carbide grains for abrasive applications

Green silicon carbide chemically treated and black silicon carbide water-washed with high purity micro grains, produced to comply with JIS standard particularly suitable for high quality vitrified bonded grinding wheels, honing stones, lapping, fine coated abrasives and special polishing applications.

Packaging 1.000 kg or 25 kg paper bags or 100 kg drums. 500 kg big bags on demand.

Typical chemistry

	SiC	Free-C	Free-SiO ₂	Free-Si	Fe ₂ O ₃	MI
SIKA® ABR I	98.50%	0.15%	0.10%	0.10%	0.10%	-
SIKA® ABR JIS - micro	98.00%	0.14%	0.75%	0.75%	-	-

Grit sizes

Grit no.	Ø d _{s50} mean µm
JIS 800	14.0
JIS 1000	11.5
JIS 1200	9.5
JIS 1500	8.0
JIS 2000	6.7
JIS 2500	5.5
JIS 3000	4.0
JIS 4000	3.0

Analytical procedures:

Particle Size distribution is measured according to FEPA Standard 42-1 for Macro-, and 42-2 for Micro-grains
 LPD = Loose Pack Density is measured according to FEPA Standard 44-1 for Macro-, and 44-2 for Micro-grains
 Magnetic Iron (MI) measured according ANSI B74.19
 Chemistry according ANSI B74.15

The information contained in this Product Information Document is the sole property of Kymera International, and cannot be distributed outside Kymera International or its Customers, entirely or by parts, without the prior consent of Kymera International. The Product Information Documents display typical characteristics for Kymera International's products as currently produced in Kymera International's various manufacturing locations. These typical characteristics do not constitute a precise Customer Specification, which has to be elaborated separately between the Customer and Kymera International in the frame of a commercial offer. Only with this precise Customer Specification can Kymera International be bound to any commitment or liability regarding the quality of its products.